

AI-1

STUDIO-QUALITY AUDIO INTERFACE
& HEADPHONE AMPLIFIER

The AI-1 is a studio-grade audio interface suitable for connecting both microphones and musical instruments to a computer or tablet. It features an ultra-low-noise preamp, a high-power headphone amplifier, and balanced line outputs. Switchable 48V phantom power facilitates the connection of condenser microphones, and zero-latency monitoring mode allows for seamless recording.

- Single channel audio interface
- 2 x 1/4" balanced line outputs
- Neutrik™ combo jack input
- 48V phantom power



48V
PHANTOM
POWER



1/4" BALANCED
LINE OUTPUTS



NEUTRIK™
COMBO JACK
INPUT



HIGH-POWER
HEADPHONE
AMPLIFIER



ACOUSTIC & ELECTRICAL SPECIFICATIONS

Computer Connectivity:	USB
Form Factor:	Desktop
Simultaneous I/O:	1 x 2
Number of Preamps:	1
Phantom Power:	Yes
Bit Depth:	24-bit
Sample Rates:	44.1 kHz 48 kHz 88.2 kHz 96kHz
Analog Inputs:	1 x Neutrik XLR-1/4" combo
Analog Outputs:	2 x 1/4" (impedance balanced) 1 x 1/4" (headphones)
Direct Monitor:	Yes
USB:	1 x USB Type C
Bus Powered:	Yes
OS Requirements:	Mac OS 10.10 or later Windows 7 or later
Power:	USB bus-powered



RØDE

MECHANICAL SPECIFICATIONS

Weight (grams):	560
Dimensions (millimetres):	Depth: 100 Width: 124 Height: 38 (with knobs, 88 without knobs)

WHATS IN THE BOX



AI1 Single Channel Audio Interface



USB-C to USB-A Cable

DIMENSIONS

